

NEW, CONTINUATION, DIVISIONAL OR
CONTINUATION-IN-PART APPLICATION
UNDER 37 C.F.R. §1.53(b)

Attorney Docket No. 7784-000135
Express Mail Label No. EL581388269US
Date August 2, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Hon. Commissioner of Patents and Trademarks
Washington, D. C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. §1.53(b) is a patent application for
SELF-COMPENSATING HYBRID COMBINATION DUCTS

identified by: ☐ First named inventor _____
or ☒ Attorney Docket No. (see above)

1. Type of Application

☒ This application is a new (non-continuing) application.

☐ This application is a ☐ continuation / ☐ divisional / ☐ continuation-in-part of prior application No. _____. Amend the specification by inserting before the first line the sentence:

--This is a [continuation/division/continuation-in-part] of United States patent application No. _____, filed _____--

☐ The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

If for some reason applicant has not requested a sufficient extension of time in the parent application, and/or has not paid a sufficient fee for any necessary response in the parent application and/or for the extension of time necessary to prevent the abandonment of the parent application prior to the filing of this application, please consider this as a Request for an Extension for the required time period and/or authorization to charge our Deposit Account No. 08-0750 for any fee that may be due. THIS FORM IS BEING FILED IN TRIPLICATE: one copy for this application; one copy for use in connection with the Deposit Account (if applicable); and one copy for the above-mentioned parent application (if any extension of time is necessary).

2. Contents of Application

a. Specification of 32 pages;

- ☐ A microfiche computer program (Appendix);
☐ A nucleotide and/or amino acid sequence submission;

☐ Because the enclosed application is in a non-English language, a verified English translation ☐ is enclosed ☐ will be filed.

☐ Cancel original claims _____ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing date purposes.)

b. ☒ Drawings on 6 sheets (Figs. 1-10);

Attorney Docket No. 7784-000135
Express Mail Label No. EL581388269US
Date August 2, 2000

- c. ☒ A signed Oath/Declaration ☒ is enclosed / ☐ will be filed in accordance with 37 C.F.R. §1.53(f).

The enclosed Oath/Declaration is ☒ newly executed / ☐ a copy from a prior application under 37 C.F.R. §1.63(d) / ☐ accompanied by a statement requesting the deletion of person(s) not inventors in the continuing application.

d. **Fees**

FILING FEE	Number				Number				Basic Fee
CALCULATION	Filed				Extra		Rate	\$690.00	
Total Claims	26	–	20	=	6	×	\$18.00	=	\$108.00
Independent Claims	5	–	3	=	2	×	\$78.00	=	\$156.00
Multiple Dependent Claim(s) Used							\$260.00	=	-0-
FILING FEE – NON-SMALL ENTITY									\$954.00
FILING FEE - SMALL ENTITY: Reduction by 1/2									
[] Verified Statement under 37 C.F.R. §1.27 is enclosed.									-0-
[] Verified Statement filed in prior application.									
Assignment Recordal Fee (\$40.00)									\$40.00
37 C.F.R. §1.17(k) Fee (non-English application)									-0-
TOTAL									\$994.00

- ☒ A check is enclosed to cover the calculated fees. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to Deposit Account No. 08-0750. A duplicate copy of this document is enclosed.

- ☐ The calculated fees will be paid within the time allotted for completion of the filing requirements.

- ☐ The calculated fees are to be charged to Deposit Account No. 08-0750. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to said Deposit Account. A duplicate copy of this document is enclosed.

3. **Priority Information**

- ☐ **Foreign Priority:** Priority based on _____ Application No. _____, filed _____, is claimed.

- ☐ A copy of the above referenced priority document ☐ is enclosed / ☐ will be filed in due course, pursuant to 35 U.S.C. §119(a)-(d).

- ☐ **Provisional Application Priority:** Priority based on United States Provisional Application No. _____, filed _____, is claimed under 35 U.S.C. §119(e).

Attorney Docket No. 7784-000135

Express Mail Label No. EL581388269US

Date August 2, 2000

4. Other Submissions

☐ A Preliminary Amendment is enclosed.

☒ An Information Disclosure Statement, 1 sheets of PTO Form 1449, and 12 patent(s)/publications/documents are enclosed.

☒ A power of attorney

☒ is submitted ☒ with the new Oath/Declaration.

☐ is of record in the prior application and ☐ is in the original papers / ☐ a copy is enclosed.

☒ An Assignment of the invention

☒ is enclosed with a cover sheet pursuant to 37 C.F.R. §§3.11, 3.28 and 3.31.

☐ is of record in a prior application. The assignment is to _____, and is recorded at Reel _____, Frame(s) _____.

☐ An Establishment of Assignee's Right To Prosecute Application Under 37 C.F.R. §3.73(b), and Power Of Attorney is enclosed.

☒ An Express Mailing Certificate is enclosed.

☐ Other: _____

Attention is directed to the fact that the correspondence address for this application is:

Harness, Dickey & Pierce, P.L.C.
P.O. Box 828
Bloomfield Hills, Michigan 48303
(248) 641-1600.

Respectfully,



Michael D. Zalobsky
Reg. No. 45,512

Date 8/2/00
Harness, Dickey & Pierce, P.L.C.
P.O. Box 828
Bloomfield Hills, Michigan 48303
(248) 641-1600

08-03-00

A



HARNESS, DICKEY & PIERCE, P.L.C.

ATTORNEYS AND COUNSELORS
P O BOX 828
BLOOMFIELD HILLS, MICHIGAN 48303

U.S.A.
Date August 2, 2000

TELEPHONE
(248) 641-1600

TELEFACSIMILE
(248) 641-0270

Hon. Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Sir:

EXPRESS MAILING CERTIFICATE

Applicant: Jayant D. Patel

Serial No (if any):

For: SELF-COMPENSATING HYBRID COMBINATION DUCTS

Docket: 7784-000135

Attorney: Mark D. Elchuk

"Express Mail" Mailing Label Number EL581388269US

Date of Deposit August 2, 2000

I hereby certify and verify that the accompanying Check in the amount of \$994.00 (\$954.00 for filing fee, \$40.00 for Assignment Recordal Fee); Transmittal Letter (in duplicate); Specification (including 32 pgs.); Drawings on 6 Sheets (Figs. 1-10); Declaration and Power of Attorney; Assignment Recordal Sheet (in duplicate); Assignment; Information Disclosure Statement; PTO Form-1449 (including 12 references) are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" service under 37 C.F.R. 1.10 on the date indicated above and (is) are addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Signature of Person Mailing Document(s)

09530902 080200

SELF-COMPENSATING HYBRID COMBINATION DUCTS

TECHNICAL FIELD

The present invention relates generally to the forming of duct assemblies
5 and more particularly to a duct assembly having an end or intermediate portion
which is specifically tailored to the needs of a particular application. The end or
intermediate portion may be relatively more flexible and self-forming than the
adjoining portion or may have a protective covering to provide the hose
assembly with a predetermined characteristic such as abrasion, tear or puncture
10 resistance in a desired area.

BACKGROUND OF THE INVENTION

BACKGROUND ART

In the aircraft industry, complex ducts are frequently required for the
15 routing of pressurized fluids, including air, throughout the aircraft. These
ducts are often times fabricated in from metal or other rigid materials in
several long sections, with each section having numerous branches for
coupling various components to the duct. An illustrative duct section
constructed in this manner is illustrated in Figure 1.

20 Duct section 10 includes a body portion 12 and a plurality of branch
portions 14. Body portion 12 and branch portions 14 are formed with
relatively expensive tools and equipment according to a design model. The
design model typically employs the nominal positions or 3-dimensional
location 16 of the components 18 that are to be coupled to the duct section

10, as well as the structure of the device into which duct section 10 is attached, to determine the geometry of the body portion 12 and each of the branch portions 14. In a typical situation, the design data for the duct section 10 that is developed from the design model is quite complex, with many
5 curves, bends and branch portions 14 being formed in the duct section 10 throughout its length.

The configuration of the duct section 10 frequently necessitates that it be fabricated in several component parts which are then coupled together via specialized fittings, clamps or welding. Those skilled in the art will readily
10 understand that due to part-to-part variation between the component parts, as well as the variation in which they are assembled, the configuration of duct section 10 can vary widely from the design model. Complicating matters is that the actual positions 20 of the components 18 that are to be coupled to the duct section 10 frequently vary from their nominal position 16.

15 If the variance between the actual position 20 of the components 18 and the associated connection point of the duct section 10 are severely misaligned, it is necessary to take corrective action, such as modifying the tooling on which the component parts of the duct section 10 are fabricated, modifying the design positions of the components 18 which are connected to duct
20 section 10, and/or reworking duct section 10 to tailor it to the particular application. These corrective actions are frequently expensive and time consuming as it is usually quite difficult to identify and quantify each of the variations from the design model. Often times, the corrective action is

iterative in nature, with small improvements being made over an extended period of time.

While the amount of time that is expended to achieve a finalized design is one drawback of an iterative design approach, another concerns the proliferation of components that result from the release of "intermediate" versions into production. As each version may have unique servicing and maintenance requirements, thereby increasing the complexity of a servicing program. Furthermore, stocking of several "intermediate" versions may be necessary to ensure that all previously produced products may be timely serviced.

One solution that has been proposed is to break the duct section into a plurality of even shorter sub-sections which are coupled together during the installation of duct section 10 into a particular application. One drawback of the use of multiple duct sub-sections is that depending on the particular application, it can be difficult to couple the sub-sections together if the duct sub-sections are relatively inaccessible for servicing after they are located into the application. This solution is also relatively expensive, can adversely affect the overall reliability of the duct section, increase the frequency with which it must be serviced and add considerable weight to the duct section.

These drawbacks are particularly true where relatively long flexible hoses are employed, as these sub-sections tend to move relative to their associated duct-subsections due to vibrations that are generated in the application and transmitted through the duct. This relative motion renders the

intersection between the duct sub-sections more susceptible to failure due to the stresses, strain and/or shear forces that are typically created in that region from the clamping device which secures the hose to its associated duct sub-section and/or abrading on another portion of the application (e.g., the
5 structure to which the duct is coupled).

Accordingly, there remains a need in the art for a duct that is relatively easy and inexpensive to fabricate regardless of the complexity of its configuration. The duct should be easy to install and readily accommodate the variation that occurs from part-to-part and application-to-application.
10 Furthermore, the duct should be easily tailored to the unique needs of an application.

SUMMARY OF THE INVENTION

In one preferred form, the present invention provides a duct assembly
15 for coupling a pair of components in fluid connection. The duct assembly includes a first portion, a second portion and a support collar. The second portion is relatively more flexible than the first portion and in fluid connection with the first portion. The support collar is coupled to an outer perimeter of the second portion and abuts the first portion. The support collar is sized to prevent
20 the formation of a stress riser at an intersection between the first and second portions to thereby render the intersection less susceptible to tearing in response to repeated flexing of the second portion.

In another preferred form, the present invention provides a duct assembly for coupling a pair of components in fluid connection. The duct assembly includes a duct portion and a sleeve portion. The sleeve portion is bonded to an exterior perimeter of the duct portion in a predetermined area of the duct portion and provides the predetermined area of the duct portion with a predetermined characteristic, such as abrasion and tear resistance.

In another preferred form, the present invention provides a method for forming a reinforced flexible duct assembly. The method includes the steps of providing a duct member; determining a diameter of the duct member; selecting a reinforcement member and a reinforcement pitch based on the diameter of the duct member; and bonding the reinforcement member to an exterior surface of the duct member in a helix such that a pitch of the helix is equal to the reinforcement pitch.

In another preferred form, the present invention provides a method for forming a hose assembly for coupling a plurality of components in fluid connection. The method includes the steps of forming a rigid duct structure and a flexible duct structure; and bonding the flexible duct structure to an end of the rigid duct structure to produce a clampless flexible joint which permits an end of the flexible duct structure opposite the rigid duct structure to be moved relative to the rigid duct structure.

In another preferred form, the present invention provides a method for forming a hose assembly for coupling a plurality of components in fluid connection. The method comprising the steps of forming a flexible duct

structure from an elastomeric material; forming first and second rigid duct structures, the first and second rigid duct structures being formed to be relatively more rigid than the flexible duct structure; coupling the first rigid duct structure to a first end of the flexible duct structure; and coupling the second rigid duct structure to a second end of the flexible duct structure such that the flexible duct structure permits the first and second rigid duct structures to be moved relative to one another.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Additional advantages and features of the present invention will become apparent from the subsequent description and the appended claims, taken in conjunction with the accompanying drawings, wherein:

Figure 1 is a plan view of a conventional prior art duct assembly;

15 Figure 2 is a plan view of a duct assembly constructed in accordance with several aspects of the present invention, the duct assembly being shown in an installed condition;

Figure 3 is a cross-sectional view taken along the line 3-3 of Figure 2;

Figures 4a, 4b, 4c, 4d, 4e & 4f are cross-sectional views of different helix members;

20 Figure 5 is an enlarged view of a portion of Figure 3 illustrating a bent portion of the intersection between the rigid and flexible duct structures when a positive pressure load is applied to the interior of the duct assembly;

Figure 6 is a view similar to that of Figure 6 but illustrating a bent portion of the intersection between the rigid and flexible duct structures when a negative pressure load is applied to the interior of the duct assembly;

Figure 7 is a cross-sectional view taken along the line 7-7 of Figure 2;

5 Figure 8 is a plan view of a duct assembly similar to that of Figure 2 but illustrating a first alternate construction;

Figure 9 is a plan view of a duct assembly constructed in accordance with another aspect of the present invention;

10 Figure 10 is a plan view of a duct assembly similar to that of Figure 9 but illustrating an alternate construction.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

002030" 2060E960
15 With reference to Figure 2 of the drawings, a duct assembly constructed in accordance with the teachings of the present invention is generally indicated by reference numeral 10. Duct assembly 10 is shown to include a plurality of rigid duct structures 52, a plurality of flexible duct structures 54 and a plurality of elastomeric attachment sleeves 56. Each of the rigid duct structures 52 is formed from a material which is relatively more rigid than the flexible duct structure 54 to which it is adjacent. For example,
20 rigid duct structures 52a and 52b are relatively more rigid than flexible duct structure 54a. In the particular embodiment illustrated, each of the rigid duct structures 52 are fabricated from metals, such as steel and aluminum, plastics and composites such as fiberglass, carbon, KEVLAR® and NEXTEL®.

Each of the flexible duct structures 54 is positioned between an associated pair of rigid duct structures 52 to permit the shape of duct assembly 50 to be easily tailored to the needs of a particular application. The flexible duct structures 54 are illustrated to be bonded to one or more associated rigid duct structures 52 to produce a clampless flexible joint that joins the opposite ends of each of the flexible duct structures 54 to an associated one of the rigid duct structures 52. In the particular embodiment illustrated, flexible duct structures 54b, 54c and 54d are helix reinforced structures 60 and flexible duct structures 54a and 54e are convoluted bellows structures 62.

A detailed description of helix reinforced structure 60 is beyond the scope of the present invention and need not be provided herein. Briefly, and with additional reference to Figures 3 through 6, each of the helix reinforced structures 60 is shown to include an inner liner or member 66, a reinforcing helix 68 and an outer member 70. In the example provided, inner member 66 and outer member 70 are formed from conventional elastomeric duct materials (i.e., uncured elastomeric impregnated composite fabrics), such as rubber, silicone, nitrile, butyl, ethylene propylene, neoprene, polyurethane, fluoro silicone and fluoro elastomers and reinforcing helix 68 is fabricated from a thermoplastic material such as polyetherimide, polyphenylsulfone or polyarylsulfone.

Reinforcing helix 68 is bonded between inner and outer members 66 and 70, thereby reinforcing inner member 66 to guard against bursting,

collapsing or kinking. The cross-section of reinforcing helix 68 preferably includes a flat base 72 as shown in Figures 4a through 4d but other shapes, such as those shown in Figures 4e and 4f may also be used. Reinforcing helix 68 may also have one or more hollow cavities 74 as illustrated in Figures 4c, 4d and 4f to reduce the weight and stiffness of duct assembly 50. Helix reinforced structure 60 is otherwise discussed in greater detail in commonly assigned U.S. Patent No. 6,000,435, the disclosure of which is hereby incorporated by reference as if fully set forth herein.

In fabricating duct assembly 50, the inner member 66 of flexible duct structure 54b is positioned to extend into the ends 78 and bonded to the inner walls 80 of rigid duct structures 52b and 52c. An adhesive material is applied to the exterior surface 82 of inner member 66 and/or to reinforcing helix 68 and reinforcing helix 68 is applied to the portion of the inner member 66 between rigid duct structures 52b and 52c. Preferably, the size of the material forming reinforcing helix 68 (i.e., the reinforcement member 84) as well as the pitch "p" of reinforcing helix 68 are related to the size of the flexible duct structure 54 in accordance with a second aspect of the present invention as shown, for example, in the table set forth below. Sizing reinforcement member 84 and setting the pitch "p" of reinforcing helix 68 to the reinforcement pitch set forth in the table, below, permits flexible duct structure 54 to achieve a good balance of strength and flexibility without the need for experimentation to empirically derive the size of the material and pitch of the helix. Proper selection of the material which forms reinforcing helix 68 and

the pitch "p" of reinforcing helix 68 permits flexible duct structure 54 to be bent with a relatively tight bending radius without kinking (illustrated by reference letter "k" in phantom in Figure 2).

007773-000135

Table 1

Diameter (d) of Flexible Duct Structure (inches)	Dimension of Polyetherimide Reinforcing Helix Material* (inches)		Reinforcement Pitch	
	Solid Cross- Section	Hollow-Cross Section	Solid Cross- Section	Hollow-Cross Section
$d > 7\frac{1}{2}$	0.15	0.15	$\frac{3}{4}$	$\frac{3}{4}$
$7\frac{1}{2} \geq d > 5\frac{1}{2}$	$\frac{1}{8}$	$\frac{1}{8}$	$\frac{3}{4}$	$\frac{3}{4}$
$5\frac{1}{2} \geq d > 4$	0.10	0.10	$\frac{7}{8}$	$\frac{7}{8}$
$4 \geq d > 3\frac{1}{2}$	0.10	0.10	$\frac{3}{4}$	$\frac{3}{4}$
$3\frac{1}{2} \geq d > 2\frac{1}{2}$	$\frac{3}{32}$	$\frac{3}{32}$	$\frac{3}{4}$	$\frac{3}{4}$
$2\frac{1}{2} \geq d > 1\frac{3}{4}$	$\frac{3}{32}$	$\frac{3}{32}$	$\frac{5}{8}$	$\frac{5}{8}$
$1\frac{3}{4} \geq d > 1\frac{1}{4}$	$\frac{5}{64}$	$\frac{5}{64}$	$\frac{1}{2}$	$\frac{1}{2}$
$1\frac{1}{4} \geq d > 1$	$\frac{1}{16}$	-	$\frac{7}{16}$	-
$1 \geq d$	$\frac{1}{16}$	-	$\frac{3}{8}$	-

*The term "dimension" is employed to describe the largest cross-sectional width dimension (e.g., diameter) of the reinforcing helix material.

Additional adhesive material may be applied to the inner surface 86 of
5 outer member 70 before outer member 70 is overlaid onto the reinforcing helix
68 and inner member 66 to complete the lay-up of this portion of duct
assembly 50. Preferably, however, the lay-up also includes a pair of support
collars 90 constructed in accordance with a third aspect of the present invention.
Support collars 90 are disposed between reinforcing helix 68 and each of the
10 rigid duct structures 52b and 52c and coupled to the exterior surface 94 of the
outer member 70.

Each of the support collars 90 are preferably fabricated from a thermoplastic material such as polyetherimide, polyphenylsulfone or polyarylsulfone. The cross-section of the support collars 90 may be solid or hollow and may be identical in configuration to reinforcing helix 68. It is preferred, however, that each of the support collars 90 have a cross-section with a rounded top 96 and a flat base 72, such as the cross-sections shown in Figures 4b and 4c. It is also preferred that the ends 78 of the rigid duct structures 52 include an end portion 100 which is smaller in diameter than a body portion 102 of the rigid duct structure 52. End portion 100 preferably has a height which is equal to the height of support collar 90 and a length which is equal to the pitch "p" of reinforcing helix 68.

In operation, support collar 90 is operable for distributing loads associated with the movement of flexible duct structure 54 relative to rigid duct structure 52, whether the movement be caused from the bending of flexible duct structure 54 or exposure to a fluid pressure differential. In Figure 5, the interior 106 of duct assembly 50 is exposed to a pressurized fluid, causing flexible duct structure 54 to bulge in an outward direction. Support collar 90 limits the amount by which the wall 108 of flexible duct structure 54 may rotate relative to rigid duct structure 52 and helps to spread the tensile and compressive forces associated with the bulging of the flexible duct structure 54 over a relatively larger area. Support collar 90 is therefore sized to prevent the formation of a stress riser at the intersection 110 between rigid duct structure 52 and flexible duct structure 54 to thereby render the intersection 110 less susceptible to

tearing or shearing in response to repeated flexing of the flexible duct structure 54.

002080" 2060E960

A similar condition is illustrated In Figure 6 wherein the interior 106 of duct assembly 50 is exposed to vacuum pressure, causing flexible duct structure 54 to bulge in an inward direction. Like the situation illustrated in Figure 5, support collar 90 limits the amount by which the wall 108 of flexible duct structure 54 may rotate relative to rigid duct structure 52 and helps to spread the tensile and compressive forces associated with the bulging of the flexible duct structure 54 over a relatively larger area. A similar condition is also experienced by flexible duct structure 54 when flexible duct structure 54 is bent relative to the longitudinal axis of rigid duct structure 52. Accordingly, support collar 90 is operable for rendering intersection 110 less susceptible to failures from the deformation of flexible duct structure 54 as a result of a differential fluid pressure as well as rendering intersection 110 less susceptible to failures from the movement or flexure of flexible duct structure 54 relative to rigid duct structure 52.

Returning to Figure 2 and with additional reference to Figure 7, each of the convoluted bellows structures 62 is shown to include a plurality of elastomeric convolutions 120, a pair of end portions 122 and a pair of external plies 124. Convoluted bellows structure 62 is formed from a suitable elastomer, such as silicone, viton, flourosilicone, nitrile or neoprene. The elastomeric material may also be coated or impregnated over a fabric such as fiberglass or kevlar, depending on various design criteria.

Each of the end portions 122 is illustrated to be generally cylindrical in shape and sized to engage the end sections 128 of the rigid duct structures 52a and 52b. External plies 124 may be formed from a material such as fiberglass reinforced silicone and are sized to overlap a portion of one of the end portions 122 and portion of an associated one of the end sections 128, permitting the external plies 124 to secure the convoluted bellows structure 62 to an associated pair of rigid duct structures 52.

The plurality of elastomeric convolutions 120 couple the end portions 122 together and are resilient enough to permit relative axial movement between rigid duct structures 52a and 52b. The convoluted bellows structures 62 are generally employed in relatively short lengths and are generally more flexible than the helix reinforced structures 60. Convoluted bellows structures 62 are typically employed to correct misalignment between the duct assembly 50 and another device (not shown), and/or to permit the length of the duct assembly 50 to be varied and/or to dampen vibrations which are transmitted through duct assembly 50. The number, shape and height of the convolutions 120 and length of the convoluted bellows structure 62 is dependent on various design criteria, such as the anticipated misalignment or desired variation in the length of duct assembly 50.

Depending on the differential fluid pressure, the fluid (e.g., air) in duct assembly 50 may exert a load on convoluted bellows structure 62 which causes the convolutions 120 to expand outwardly, possibly restricting the flow of fluid through duct assembly 50 and/or permitting the convoluted bellows

structure 62 to rub and abrade on another component and in severe cases, rupture. Accordingly, a reinforcing material, such as a plurality of thermoplastic or metal reinforcing collars 132, may be incorporated into convoluted bellows structure 62 to locally control the expansion of the convolutions 120.

5 Returning to Figure 2, each of the attachment sleeves 56 is illustrated to be bonded to an associated one of the rigid duct structures 52 and is employed where additional stiffness is required, as for example where the ends 150 of duct assembly 50 are clamped to another device. Each of the attachment sleeves 56 is fabricated in a multi-ply manner wherein one or
10 more rigid layers 200 are wrapped around an inner flexible layer 202.

 The rigid layers 200 may be formed from a polyester impregnated fiberglass, for example, and the inner flexible layer 202 may be formed from an elastomeric material such as silicone. In the particular example provided, the silicone inner flexible layer 202 is heat resistant and operable for forming a
15 gasket that contains pressurized fluids within duct assembly 50, while the polyester impregnated fiberglass rigid layers 200 is suitable for withstanding the dynamic loading and motions that are transmitted through attachment sleeve 56.

 In forming duct assembly 50, it is preferred that a lay-up of the entire
20 duct assembly 50 (i.e., the rigid duct structures 52 be coupled to their respective flexible duct structures 54 and attachment sleeves 56) and duct assembly 50 be co-cured in an oven or autoclave in a single cycle. However, those skilled in the art will also understand that each of the flexible duct

structures 54 and attachment sleeves 56 may be pre-cured as necessary and subsequently bonded to one or more of the associated rigid duct structures 52.

Forming duct assembly 50 with flexible duct structures 54 and attachment sleeves 56 is highly advantageous as compared with the duct structures of the prior art because the flexible duct structures 54 permit the rigid duct structures 52 to be fabricated in relatively straight sections, thereby reducing tooling and labor costs associated with the fabrication of duct assembly 50. Furthermore, as flexible duct structures 54 provide a comparatively large degree of latitude in the position of the ends 150 of duct assembly 50, the process of installing duct assembly 50 into an application is considerably easier and faster.

In Figure 8, duct assembly 50a is illustrated to be similar to duct assembly 50 in that it includes a flexible duct structure 54 and a plurality of rigid duct structures 52. However, duct assembly 50a includes a plurality of attachment sleeves 56a which have a beaded end portion 220 that is operable for engaging the inner diameter 222 of a coupling hose 224. A retaining ring 226 is slid along the outer surface 228 of coupling hose 224 until it passes over beaded end portion 220.

The geometry of retaining ring 226 provides anti-slip resistance to coupling hose 224, preventing coupling hose 224 from detaching from the beaded end portion 220 of hose assembly 50a. Pressurized fluid introduced into duct assembly 50a generates a detaching force causing coupling hose

224 and retaining ring 226 to separate from duct assembly 50a until a curved portion 230 of retaining ring 226 makes contact with beaded end portion 220. Additional detaching force then acts to squeeze retaining ring 226 and coupling hose 224 against beaded end portion 220, thereby creating a seal
5 between coupling hose 224 and duct assembly 50a. Beaded end portion 220 and retaining ring 226 are discussed in greater detail in above-referenced U.S. Patent No. 6,000,435.

In Figure 9, a portion of a duct assembly constructed in accordance with the teachings of a fourth aspect of the present invention is generally
10 indicated by reference numeral 50b. Duct assembly 50b is shown to include a duct structure 250 and a sleeve member 252. In the particular embodiment illustrated, duct structure 250 is a helix reinforced structure 60 constructed in the manner discussed above and not necessarily coupled to a rigid duct structure 52. However, those skilled in the art will understand that the
15 teachings of this aspect of the present invention may be applied to other types of duct structures including rigid duct structures 52. As such, the scope of this aspect of the present invention will not be limited to duct structures having a helix reinforced structure 60.

Sleeve member 252 includes a hollow central cavity (not specifically
20 shown) which is sized to receive helix reinforced structure 60. Sleeve member 252 is slid over duct structure 250 to a predetermined area of helix reinforced structure 60 and bonded to the exterior perimeter 256 of helix reinforced structure 60. The ends 258 of sleeve member 252 may be secured

to a lay-up of helix reinforced structure 60 via several plies of material 260 that are bonded to sleeve member 252 and helix reinforced structure 60. Thereafter, hose assembly 50b is placed in an oven at an elevated temperature to permit the adhesive that bonds helix reinforced structure 60
5 together as well as adhesive that bonds sleeve member 252 to helix reinforced structure 60 to be simultaneously cured.

Sleeve member 252 is operable for providing the portion of duct structure 250 to which it is coupled a predetermined one or more predetermined characteristics, such as abrasion resistance, puncture
10 resistance or additional strength. If abrasion resistance is required, sleeve member 252 may be formed from a material such as polyester or KEVLAR®. If puncture resistance or additional strength is required, sleeve member 252 may be formed from a woven material, such as steel wire, carbon graphite or KEVLAR® or from a material such as NEXTEL®. If heat resistance or
15 containment is required, sleeve member 252 may be formed from a material such as NEXTEL®.

In Figure 10, an alternative method for constructing hose assembly 50b is illustrated wherein helix reinforced structure 60 is be pre-formed and cured prior to the application of sleeve member 252 to helix reinforced structure 60
20 and the curing of adhesive 270 which couples sleeve member 252 to helix reinforced structure 60. This situation is most likely to arise when duct structure 250 is in need of repair or reworking. In such situations, the repair/rework operation is frequently performed when the duct assembly 50b

is partially installed in its operating environment and as such, it is frequently not possible to cure the adhesive in an oven. Accordingly, a silicone adhesive, such as a room-temperature vulcanizing (RTV) silicone adhesive, may be employed to bond sleeve member 252 to duct structure 250.

5 While the invention has been described in the specification and illustrated in the drawings with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention as defined in the claims. In addition, many modifications may be
10 made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment illustrated by the drawings and described in the specification as the best mode presently contemplated for carrying out this invention, but that the invention will include
15 any embodiments falling within the foregoing description and the appended claims.

WHAT IS CLAIMED IS:

1. A duct assembly for coupling a pair of components in fluid connection, the duct assembly comprising:

a first portion;

a second portion in fluid connection with the first portion, the second
5 portion being relatively more flexible than the first portion; and

a support collar coupled to an outer perimeter of the second portion and
abutting the first portion, the support collar being sized to prevent the formation
of a stress riser at an intersection between the first and second portions to
thereby render the intersection less susceptible to tearing in response to
10 repeated flexing of the second portion.

002020 "2050350

2. The duct assembly of Claim 1, wherein the support collar has a cross-section with a generally flat base.
3. The duct assembly of Claim 1, wherein the support collar has a generally circular cross-section.
4. The duct assembly of Claim 1, wherein the support collar has a generally hollow cross section.
5. The duct assembly of Claim 1, wherein the second portion includes a reinforcing helix that is positioned to abut the support collar.
6. The duct assembly of Claim 5, wherein an end of the first portion proximate the intersection has an end portion which is smaller in diameter than a body portion of the first portion.
7. The duct assembly of Claim 6, wherein the diameter of the end portion is approximately equal to an outside diameter of the support collar.
8. The duct assembly of Claim 7, wherein the length of the end portion is equal to a pitch of the reinforcing helix.

a duct portion; and

5 sleeve portion being coupled to a predetermined area of the duct portion and
providing the predetermined area with a predetermined characteristic.

10. The duct assembly of Claim 9, wherein the sleeve portion is formed from polyester and the predetermined characteristic is abrasion resistance.

11. The duct assembly of Claim 9, wherein the sleeve portion is formed from a woven material.

12. The duct assembly of Claim 9, wherein the sleeve portion is formed from a material selected from a group of materials consisting of steel, carbon graphite, kevlar and nextel.

13. The duct assembly of Claim 9, wherein the duct portion is formed from a plurality of plies that are bonded together with a first adhesive material and the sleeve portion is bonded to the duct portion with a second adhesive material, the duct assembly being fabricated in a manner such that the first and
5 second adhesive materials are cured in a common curing process.

14. The duct assembly of Claim 9, wherein the duct portion is formed from a plurality of plies that are bonded together with a first adhesive material and the sleeve portion is bonded to the duct portion with a second adhesive material, the duct assembly being fabricated in a manner such that the first
5 adhesive material is cured prior to the curing of the second adhesive material.

15. The duct assembly of Claim 14, wherein the second adhesive material is a silicone adhesive.

002030" 2050E360

5

determining a diameter of the duct member;

bonding the reinforcement member to an exterior surface of the duct
 er in a helix such that a pitch of the helix is equal to the reinforcement

17. The method for forming a reinforced flexible duct assembly of Claim 16 wherein the step of selecting the reinforcement member and the reinforcement pitch include the steps of:

selecting a reinforcing member having a diameter of about 0.15 inch and
5 setting the reinforcement pitch equal to about three-quarters ($\frac{3}{4}$) of an inch if the diameter of the duct member is greater than seven and one-half ($7\frac{1}{2}$) inches;

otherwise, selecting a reinforcing member having a diameter of about one-eighth ($\frac{1}{8}$) inch and setting the reinforcement pitch equal to about three-quarters ($\frac{3}{4}$) of an inch if the diameter of the duct member is greater than five
10 and one-half ($5\frac{1}{2}$) inches;

otherwise, selecting a reinforcing member having a diameter of about 0.10 inch and setting the reinforcing pitch equal to about seven-eighths ($\frac{7}{8}$) of an inch if the diameter of the duct member is greater than four (4) inches;

otherwise, selecting a reinforcing member having a diameter of about
15 0.10 inch and setting the reinforcing pitch equal to about three-quarters ($\frac{3}{4}$) of an inch if the diameter of the duct member is greater than about three and one-half ($3\frac{1}{2}$) inches;

otherwise, selecting a reinforcing member having a diameter of about three-thirty-seconds ($\frac{3}{32}$) of an inch and setting the reinforcing pitch equal to
20 about three-quarters ($\frac{3}{4}$) of an inch if the diameter of the duct member is greater than about two and one-half ($2\frac{1}{2}$) inches;

otherwise, selecting a reinforcing member having a diameter of about three-thirty-seconds ($\frac{3}{32}$) of an inch and setting the reinforcing pitch equal to

about five-eighths ($5/8$) of an inch if the diameter of the duct member is greater

25 than about one and three-quarters ($1\frac{3}{4}$) inches;

otherwise, selecting a reinforcing member having a diameter of about five-sixty-fourths ($5/64$) of an inch and setting the reinforcing pitch equal to about one-half ($1/2$) inch if the diameter of the duct member is greater than about one and one-quarter ($1\frac{1}{4}$) inches;

30 otherwise, selecting a reinforcing member having a diameter of about one-sixteenth ($1/16$) of an inch and setting the reinforcing pitch equal to about seven-sixteenths ($7/16$) if the diameter of the duct member is greater than about one (1) inch; and

otherwise, selecting a reinforcing member having a diameter of about
35 one-sixteenth ($1/16$) of an inch and setting the reinforcing pitch equal to about three-eighths ($3/8$).

18. A method for forming a hose assembly for coupling a plurality of components in fluid connection, the method comprising the steps of:

forming a rigid duct structure and a flexible duct structure; and

bonding the flexible duct structure to an end of the rigid duct structure to

5 produce a clampless flexible joint which permits an end of the flexible duct structure opposite the rigid duct structure to be moved relative to the rigid duct structure.

002030 " 20506360

19. The method of Claim 18, further comprising the steps of:
providing an elastomeric attachment sleeve; and
bonding the elastomeric attachment sleeve to an end of the rigid duct structure opposite the flexible duct structure.

20. The method of Claim 18, wherein the flexible duct structure includes a plurality of bellows.

21. The method of Claim 20, wherein the plurality of bellows are reinforced with a reinforcing member.

22. The method of Claim 21, wherein the reinforcing member is formed from a thermoplastic.

23. The method of Claim 18, wherein an end of the rigid duct structure includes a beaded end portion.

24. The method of Claim 18, wherein the rigid duct structure is formed from a material selected from a group of materials consisting of metals, plastics and composites.

25. A method for forming a hose assembly for coupling a plurality of components in fluid connection, the method comprising the steps of:

forming a flexible duct structure from an elastomeric material;

forming first and second rigid duct structures, the first and second rigid
5 duct structures being formed to be relatively more rigid than the flexible duct structure;

coupling the first rigid duct structure to a first end of the flexible duct structure; and

coupling the second rigid duct structure to a second end of the flexible
10 duct structure such that the flexible duct structure permits the first and second rigid duct structures to be moved relative to one another.



002020 "2060E960

26. The method of Claim 25, further comprising the steps of:
providing an elastomeric attachment sleeve; and
bonding the elastomeric attachment sleeve to an end of the second rigid
duct structure opposite the flexible duct structure.

002080" 20502360

ABSTRACT OF THE DISCLOSURE

5 A hose assembly for coupling a plurality of components in fluid connection and a method for making same. According to a first aspect of the invention, the hose assembly includes at least one rigid portion and at least one flexible portion which cooperate to permit the shape and size of the hose assembly to be easily modified so that the components may be coupled to one another. A second aspect of the invention provides a method for
10 reinforcing a flexible portion of the hose assembly to prevent the flexible portion from kinking when the flexible portion is bent. A third aspect of the invention provides a support collar for use in reinforcing an intersection between a pair of duct sections wherein at least one of the duct sections is moveable relative to the other duct section. The support collar reinforces the
15 intersection and helps to render this section less susceptible to tearing. A fourth aspect of the invention provides a hose assembly having a sleeve member which covers at least a portion of a duct member so as to provide the duct member with a predetermined characteristic, such as abrasion, tear or puncture resistance.






Fig-2




Fig-4a




Fig-4b




Fig-4c




Fig-4d




Fig-4e




Fig-4f




Fig-5

Fig-7




Fig-6




Fig-8




Fig-9




Fig-10

DECLARATION AND POWER OF ATTORNEY

Boeing reference: 00-089 (007773)
Attorney Docket No. 7784-000135

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

SELF-COMPENSATING HYBRID COMBINATION DUCTS

the specification of which (check one)

☒ [X] is attached hereto.

☐ [] was filed on _____ as Application
Serial No. _____ and was amended on
_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information that is material to the patentability of the invention claimed in this application, or information that is material to the examination of this application, in accordance with Title 37, Code of Federal Regulations, section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, section 119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

			<u>Priority Claim</u>	
(Number)	(Country)	(Day/Month/Year filed)	Yes	No
_____	_____	_____	_____	_____
(Number)	(Country)	(Day/Month/Year filed)	Yes	No
_____	_____	_____	_____	_____
(Number)	(Country)	(Day/Month/Year filed)	Yes	No
_____	_____	_____	_____	_____

DECLARATION AND POWER OF ATTORNEY

I hereby claim the benefit under Title 35, United States Code, '119(e) of any United States Provisional application(s) listed below:

PRIOR PROVISIONAL APPLICATIONS

(application serial number)

(Month / Day / Year filed)

(application serial number)

(Month / Day / Year filed)

I hereby claim the benefit under Title 35, United States Code, section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status - patented, pending, abandoned
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint Charles T. Silberberg, Reg. No. 26,584; Harry B. Field, Reg. No. 27,880; Lawrence N. Ginsberg, Reg. No. 30,943 and Thomas W. Hennen, Reg. No. 27,798 of The Boeing Company, Seattle, King County, Washington; and Mark D. Elchuk, Reg. No. 33,686 and each principal, attorney of counsel, associate and employee of Harness, Dickey & Pierce, P.L.C., who is a registered Patent Attorney, my attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. I request the Patent and Trademark Office to direct all correspondence and telephone calls relative to this application to Harness, Dickey & Pierce, P.L.C., P. O. Box 828, Bloomfield Hills, Michigan 48303 (248) 641-1600.

Full name of sole or first inventor: Jayant D. Patel

Inventor's signature: Jayant D. Patel

Date: August 1, 2000

Residence: 21221 Calle Olivia, Lake Forest, California 92630

Citizenship: United States of America

Post Office Address: 21221 Calle Olivia, Lake Forest, California 92630